



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 :

A61M 25/01

A1

(11) International Publication Number:

WO 00/53250

(43) International Publication Date: 14 September 2000 (14.09.00)

(21) International Application Number: PCT/US99/30974

(22) International Filing Date: 23 December 1999 (23.12.99)

(30) Priority Data:

PP 9075

8 March 1999 (08.03.99)

AU

(71) Applicants (for all designated States except US): BAXTER INTERNATIONAL INC. (US/US); One Deerfield Parkway, Deerfield, IL 60015 (US). ENDOGAD RESEARCH PTY LIMITED [AU/AU]; P.O. Box M88, Camperdown, NSW 2050 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WHITE, Geoffrey, H. [AU/AU]; 22 Nicholson Street, East Balmain, NSW 2041 (AU). YU, Weyun [AU/AU]; Apt. 59 #8, Brichgrove, NSW 2041 (AU). FOSTER, Stu [US/US]; 1402 East Alton Parkway, Irvine, CA 92614 (US).

(74) Agents: GLUCK, Peter, J. et al.; Baxter Healthcare Corporation, 17221 Redhill Avenue, Irvine, CA 92614 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

## Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DIRECTIONAL GUIDEWIRE



## (57) Abstract

A Directable Medical Guidewire having two ends and an outer surface for insertion through a lumen comprising: an elongate resiliently flexible body having a main portion biased into a first configuration; and, an end portion contiguous with one end of the main portion defined by a curved configuration having a first section with a first curvature and a second section having a second different curvature to that of the first section.